

# DEX 40W

## Streetlight PE Cell

The Dex Streetlight Range are designed for exterior applications where design and style matters. Dex 40W Streetlight with PE Cell works by turning on automatically, once the light level drops below a certain level. Suited for carparks, boardwalks and common thoroughfares.



### SPECIFICATIONS

#### Material Specifications

<b>Material</b>	Die-cast High Grade Aluminium
<b>Colour</b>	Corrosion Resistant Powder Coat, Black
<b>Dimensions</b>	620mm (L) x 260mm (W) x 101mm (H)
<b>Spigot Size</b>	53mm (Dia)
<b>Ingress Protection</b>	IP65
<b>Impact Rating</b>	IK09
<b>Warranty</b>	5 Year Replacement

#### Electrical Specifications

<b>Power Supply</b>	Integral Sosen Driver, Non-Dimmable
<b>Benefits</b>	In-built PE Cell
<b>Connection Method</b>	Hard Wiring
<b>Input Voltage</b>	240V
<b>Operating Temperature (Ta)</b>	-25°C to +45°C

#### Optic Specifications

<b>Light Source</b>	1pc 40W Epistar COB
<b>Beam Angle</b>	150°
<b>Delivered Lumens</b>	5114lm
<b>Correlated Colour Temperature</b>	5700K
<b>CRI</b>	80Ra
<b>Rated Lifetime (L70B20)</b>	40,000 Hrs

### VARIATIONS

<b>LC6514</b>	DEX 40W Streetlight with PE Cell, Black, Non-Dim, 5700K
---------------	---

**dynamic series**

Efficient. Cutting Edge. Reliable

