

NEO-G Micro 2W

IP68 Ground Light

Lifestyle Series

Style. Attitude. Luxury

The NEO-G Micro 2W LED Ground Lights are marine grade quality, covered with a five year warranty. Capable of being completely submerged, these lights are great for pools, driveways, ponds and decks. Can be installed in concrete or gravel. 8mm tempered glass lens supports 1000kg drive over, manufactured with high quality anodised aluminium outer casing. These LED recessed fittings have a stainless steel (316L) front face protecting them from water including salt water and general corrosion. This product is not dimmable.



IP68



Not Dimmable

SPECIFICATIONS

Material Specifications

Housing	Die-cast aluminium with tempered glass and type 316 stainless steel cover
Mounting	Recessed In-ground (installation tube included)
Dimensions	55mm (Dia) x 84mm (H)
Cutout	40mm Dia (51mm with blackout)
Ingress Protection	IP68
Impact Rating	IK10
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	IP67 External, Sold Separately
Dimming	Non-Dim
Input Voltage	12-24V DC constant voltage
Connection Method	2-core double-insulated cable
Max. Loading	20 units per power feed
Max Distance From Power Supply	10 metres recommended

Optic Specifications

Light Source	2W CREE LED
Delivered Lumens	120lm
Beam Angle	40° (15°, 25°, Frosted Lens Options)
Reported L70 (Hours)	> 54,000 Hrs

VARIATIONS

LC5089	NEO-G Micro 2W Ground Light, 40°, 3000K
LC5189	NEO-G Micro 2W Ground Light, 40°, 4000K

